

Page 1 / 8

Issue Date: Nov in 2023 (Ver.6) Issue No.DYMSDS005-1 东东溢新材料科技有限公司 GUANGDONG DONGYI HIGH-TECH MATERIAL SCIENCE&TECHNOLOGY CO., LTD. Tel: 0760-88892754 Fax: 0760-88892744 1产品与公司信息 **1Chemical Product and Company Information** 品名:无卤聚酰亚胺覆盖膜 Product Name: Halogen-free PI Coverlay `型号代码: DCIB Type NO: DCIB 厂商:广东东溢新材料科技有限公司 Manufacturer: GUANGDONG DONGYI HIGH-TECH MATERIAL SCIENCE&TECHNOLOGY CO., LTD. 地址: 广东省中山市南区昌盛路 22 号/板芙镇智创路1号 Factory Address: No. 22 Changsheng Road, South District, Zhongshan City, Guangdong Province/ No. 1 ZhiChuang Road, Banfu Town 24小时紧急电话: 0086-0760-88892754 Emergency Telephone (24 hr): 0086-0760-88892754 般安规信息: 0086-0760-88892754 General Safety Information: 0086-0760-88892754 2物理及化学性质 2 Physical & Chemical Properties 物质状态: 固态 Physical State: Solid 气味和颜色:黄色~浅棕色 Odor And Appearance: Yellow, light brown 沸点: N/A **Boiling Point:** Not Available 分解温度: N/A Not Available Melting Point: 闪火点 N/A Flash PointNot Available 溶解度: N/A Water Solubility: Insoluble PH 值: N/A PH: Not Available 蒸汽压: N/A Vapor Pressure (mmHg): Not Available 蒸汽密度: N/A Vapor density: Not Available 爆炸界限: N/A Explosion limit: Not Available 自燃温度: N/A

Page 2 / 8

Property values are typical values. The data provided herein is for information purposes only. Each user of the material should perform their own tests to determine the suitability of the material for their particular application.

Autoignition temperature: Not Available

	1/2		学成分 composition	>	
名称: Name:					
	 脂接着剂(55%~(5	Q
Epoxy	adhesive (55%~6 序号	成分	重量百分比(%)	CAS 号	
	Number	Composition	Quality percentage (%)	CAS NO.	
		环氧树脂 Epoxy resin	38~63	25036-25-3	
	2	氢氧化铝 Aluminum Hydroxide	27~17	21645-51-2	
	3	丁腈橡胶 Chemigum	30~22	9003-18-3	
	4	促进剂 Promoting Agents	1~2	461-58-5	
		CAS 号 31975-60-7 6)CAS NO.31975-60-7		Y'Y	
		E的禁用物质及卤素要求 h RoHS and halogen fr		Tz	X
1A					
2	X		5		
		Ľ.	X	12-	

~

L > 2

Page 3/8Property values are typical values. The data provided herein is for information purposes only. Each user of the material should perform their own tests to determine the suitability of the material for their particular application.

Issue Data: Nos	v in 2023 (Ver.6)		Issue No.DYMSDS005-1
Issue Date. No		业利于古田	
一東	益 / 东东渔新州	料科技有限。	公可
DON	GUANGDONG DONGYI HIGH-TECH M Tel: 0760-88892754	TATERIAL SCIENCE& TECHNOLOG Fax: 0760-888927	
		کے لیار جو بے ایک لوار	
▲ ● ● 日 日 日 日 日 日 日 日 日 日 日 日 日	4 福 ⊼ €低于 10℃的低温,湿度 70%以下密	定性及反应性 医封键方 健方期为3个日	17-
	stable below 10°C and relative h		
反应性:温质	€低于10℃,湿度70%以下的冷库条	、件下密封储存,无明显反应	<u></u> <u> </u> <u> </u>
Reactivity:	No obvious reactionin refriger	ration storagebelow 10℃	and relative humidity lower
	than 70% conditions. +: 材料温度高于 125℃将会产生分	密.	C ×
	To Avoid: Material will decom		shigher than 125℃.
	5 :避免与氧化剂、强酸、强碱性化		
	Avoid: oxidizing agent, strong a 在一般生产条件下未有有害分解物		nic reagent, dust elimination
	在 成主) 新什下本有有苦分醉物 ecomposition: None at normal pu		
		J I	
L	XX		
		去宝 枷氏	
		有害物质信息	
 急毒性:	N/A	ards Properties	25.
		X	
Rule Floure	t Toxicity Data:Not Available N/A		
w 明 尼 舌: Eye Irritation			
Lye Initation 局部过敏:			
同时过载: Skin Irritation	N/A		
皮肤危害量:	N/A		
Dermal :Not .			
吸入危害量:	N/A Not Available		
Ingestion:	Not Available		
食入危害量:	N/A		
Inhalation:	Not Available		
L			
		· / ×	
		· X ·	
. 7,2			Y N
AY.			
		▲	
	N N	*	
	P	Page 4 / 8	
Property values	are typical values. The data provided her	rein is for information purposes	s only. Each user of the material

should perform their own tests to determine the suitability of the material for their particular application.

 \wedge

Issue Date: Nov in 2023 (Ver.6)		Issue No.DYMSDS005-1
	大洲东村州利井古阳八	*
東溢ノホン	东溢新材料科技有限公 ONGYI HIGH-TECH MATERIAL SCIENCE& TECHNOLOGY	Г Н Ј
	0760-88892754 Fax: 0760-88892744	CO., LID.
	6 注意事项	
tw m	6Warning	
概要: Overview:		
	伽馬 日王沄沈, 廿五合迭武人自和环接影响	一般使用、接触时无须特别
本厂而田丁小云厂生挥及性 注意。	物质,且无污染,故不会造成人身和环境影响。	一放使用、按触可儿须行加
	n a personal and environmental impact, due to no po	
wolatile substances, Generally 眼睛:无气味刺激眼睛,注意	y do not need to pay special attention to when using 音防喵晒粒温 λ 阻哇	, contact.
	思ル展初型及入転用。 rilling and milling operations may cause irritatior	n or injury due to mechanical
action.	行動海和大洋	
皮肤:皮肤接触不会产生任 Skin: Powder from trimming.	門刺激和小垣。 drilling and milling operations may cause skin irri	tation.
食入:本产品一般无食入的	可能和危险。	
Ingesting: Not acutely toxic 吸入:本产品一般无吸入的		
	ating to the respiratory tract.	
致癌物质:		X
Chronic/Carcinogenic: NTP: Not Tested	· /X · ·	
OSHA: Not Regulated	\sim	
IARC: Not Listed 医学制约:此产品无已知的	健康影响。	
	are no known human health effects aggravated to t	his product.
	7 急救措施	
	7.First Aid Measures	
眼睛: 立即使用大量清水冲洗:	至少15分钟,如果症状持续,立刻寻求医疗帮	助。
	ge amounts of water for at least 15 minutes. If sym	
help immediately		
皮肤:用肥皂和凉水清洗净皮质		17-
Skin: Wash with soap and cold $(A = 1)$	water to prevent dust from entering skin pores.	
▲ 食入:本产品一般无食入的可能 ■ Ingestion: Not probable		
吸入:如果吸入粉尘呼吸困难,	Ť.	
Inhalation: Dust - if breathing b	becomes impaired, seek medical attention.	
Y XX		
47		
XX		
	<u> </u>	

Issue Date: Nov in 2023 (Ver.6) Issue No.DYMSDS005-1 东东溢新材料科技有限公司 GUANGDONG DONGYI HIGH-TECH MATERIAL SCIENCE&TECHNOLOGY CO., LTD. Tel: 0760-88892754 Fax: 0760-88892744 8 灭火措施 **Fire Fighting Measures** 8 消防: 应具备完善的防护面具和防护服装。 Firefighting: Should have perfect protective mask and protective clothing. 灭火的媒介:喷水和泡沫,水是最佳的灭火媒介。不建议使用二氧化碳和干粉灭火,因其缺乏冷却能力而 可能使得重燃。 Extinguishing Media: Water spray foam. And water are the best extinguishing medium. Carbon dioxide and dry chemical are not generally recommended because their lack of cooling capacity may permit re-ignition. 有害燃烧物: -氧化碳、浓烟和微尘。 Hazardous Combustion Products: Hydrogen bromide. Formaldehyde, carbon monoxide, dense smoke and soot can be released while burning. 闪火点: N/A Flash Point: Not Established 最低燃烧极限: N/A Lower Flammable Limit: Not Established. 最大燃烧极限: N/A Upper Flammable Limit: Not Established. 燃烧条件:持续的火源。 Conditions Of Flammability: Requires continuous flame source to ignite. 静电:静电对产品未有较大影响。但静电对生产操作过程中所产生的微尘较为敏感。 Static Discharge: The product isn't sensitive to static discharge. Dust generated during trimming, drilling and milling operations may be sensitive to static discharge. 净化说明 9 **Cleaning Instruction**

常规: 注意! 请勿在生产过程中产生大量的微尘,否则采用相关回收设备避免该情况的产生。 General: Warning! During trimming, drilling and milling operations do not create dust cloud. Use collection methods such as vacuum and place into proper container for disposal or recovery.

10 处理办法

10 Handling Instruction

处理:采用完善的工业清洁设施,在生产操作过程中尽量减小微尘的吸入量,并充分透气。 Handling: Use good industrial hygiene practices. During trimming, drilling and milling operations minimize inhalation of dusts and contact with skin and eyes. Provide adequate ventilation.

储存:应避开潮湿、热源。

Stage: Store in a dry place away from moisture, excessiveheat sources.

Page 6 / 8

Issue Date: Nov in 2023 (Ver.6) Issue No.DYMSDS005-1 东东溢新材料科技有限公司 GUANGDONG DONGYI HIGH-TECH MATERIAL SCIENCE&TECHNOLOGY CO., LTD. Tel: 0760-88892754 Fax: 0760-88892744 н. 11 生产安全事项 **Operational Safety Instruction** 11 建议工作场所保持连续供应新鲜空气,采用完善的除尘设备以及相关的防护措施避免与微尘的接触。 加工 粉尘可能是火灾隐患;需定期从排气的容器,管道系统和其他表面清除灰尘。 A continuous supply of fresh air to the milling operations workplace together with removal of process dust through exhaust systems is recommended. Processing dust may be a fire hazard; remove periodically from exhaust hoods, ductwork and other surfaces using appropriate personal protection. 个人防护: Personal Protection: 眼睛/脸部: 配戴防护眼镜和防护面具。 Eye/Face: Wear safety glasses with side shields or chemical goggles during trimming, drilling and milling operations. 呼吸: 裁切时,钻孔和铣削粉尘没有充分控制的,使用呼吸防护用具。 Respiratory: When trimming, drilling and milling dusts are not adequately controlled, use respirator approved for protection from dust 生产操作:可在普通室内环境条件下操作。 Production operation: production under the condition of common indoor environment is available. 12 环境影响 12 **Environmental Effect** 常规:无相关重大的环境影响。 General: Not expected to present any significant ecological problems. 13 废弃物处理方法 13 **Disposal of Discad** 有毒废物: N/A Hazardous waste: Product is not a Hazardous Waste. 废物处理:废弃物处理请符合当地的法律法规。 Waste Disposal: Waste disposal shall comply with local laws and regulations.

Page 7 / 8

